

Emisor:

Enviar a:

### PIENSA APPLIED TECHNOLOGIES S.A.

Av. Américo Vespucio 1385 (Spacioflex), Módulo 33 –  
Quilicura – Santiago  
Chile

Teléfono: +56 2 2603 5423

Correo: cotizaciones@patindustrial.com

Web: http://www.patindustrial.com

### Unilever De Argentina

S.A. RUTA 8 Km, 60, CALLE 8 ENTRE 5 Y 9, (B1630 CFA),  
PARQUE INDUSTRIAL PILAR  
Pilar  
Argentina

Importes visualizados en Dólares USA

Descripción	IVA	P.U.	Cant.	Total (Base imp).
<p>PATN-0000008 - Transportador de correa curvo en S Origen: México.</p> <p>FlexMove Solutions Flexible Chain Conveyor Package. 260mm wide, Plain Chain, non-accumulation application, Type 05 - 38mm Aluminum high side Profile, Heavy Load, direct mount, 60 Hz Gearmotor, with Dorner stands. Includes US English documentation.</p> <p>Includes the following modules:            (74) FASR-25U. UHMW-PE Slide rail, white colour            (29) FVPC-5. Standard plain chain            (1) FMM013LDS423EN. Gearmotor, Direct Drive, LH, 130 RPM, 230/460V 60 Hz. With a chain speed of 8.7-52.3 m/min (28.6-171.5 ft/min).            (1) FMS11M260-00325P0505-01 FlexMove Solutions Idler Module, 260mm wide x 325mm (12.8in) long, Standard Idler with Power Transfer Side A, 05 - 38mm Aluminum high side Profile in A and D side.            (1) FMS1PM260-807250845H Support Stand, Horizontal Mount, 725mm (28.54in) to 845mm (33.27in) TOB. 80mm beam.            (1) FMS12M260-0907L0505-02 FlexMove Solutions Plain Corner with a 700mm radius, 260mm wide, 90 Degree Angle, 05 - 38mm Aluminum high side Profile in A and D side.            (1) FMS13M260-001650505-03 Intermediate Module, 260mm wide x 165mm (6.5in) long, 05 - 38mm Aluminum high side Profile in A and D side.            (1) FMS12M260-0907R0505-04 FlexMove Solutions Plain Corner with a 700mm radius, 260mm wide, 90 Degree Angle, 05 - 38mm Aluminum high side Profile in A and D side.            (1) FMS1PM260-807250845H Support Stand, Horizontal Mount, 725mm (28.54in) to 845mm (33.27in) TOB. 80mm beam.            (1) FMS15M260-00675PA0F0505-05 FlexMove Solutions Drive Module, 260mm wide x 675mm (26.57in) long, Direct End Drive with Power Transfer Side D, 20mm (0.79in) Drive shaft in position A, 05 - 38mm Aluminum high side Profile in A and D side.            (1) FMS1PMD26-807250845H Support Stand, Drive Mount, 725mm (28.54in) to 845mm (33.27in) TOB. 80mm beam.</p>	0%	15.816,00	1	15.816,00
<p>Variador de frecuencia Allen Bradley PowerFlex 525 1 HP - 230V. Tarjeta adicional de red Ethernet/IP. Materiales eléctricos varios</p>	0%	1.048,00	1	1.048,00
<p>Importación México a Chile. Marítimo consolidado. (estimado)</p>	0%	2.203,00	1	2.203,00

Integración VDF / Instalación en PAT / Pruebas FAT / Instalación en planta.	0%	955,00	1	955,00
---	----	--------	---	--------

**Condiciones de pago:** Pago 50% por adelantado, 50% a la entrega

Total (Base imp). 20.022,00

**Total** 20.022,00

Aceptación por escrito, sello de la empresa, fecha y firma